


LAKEWAY AIRPARK (3R9)

BNDIA THREE DEPARTURE (RNAV)



TAKEOFF MINIMUMS:

Rwy 16: 500-2\(^3\)4 or standard with minimum climb of 265' per NM to 1500.

Rwy 34: Standard.

NOTE: Chart not to scale.



22 FEB 2024

ō

21 MAR 2024

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 16: Climb on heading 165° to 1700, then as assigned by ATC for vectors to cross GARDS at or above 5000, thence....

TAKEOFF RUNWAY 34: Climb on heading 345° or as assigned by ATC for vectors to cross GARDS at or above 5000, thence....


....on track 224° to BNDIA. Maintain altitude assigned by ATC. Expect filed altitude 10 minutes after departure.

heading 165° prior to turning for obstacle avoidance.

22 FEB

ಠ


21 MAR 2024



(RNAV)

H

OUR DEPARTURE



V

LAKEWAY, TEXAS LAKEWAY AIRPARK (3R9)

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 16: Climb on heading 165° to 1700, then as assigned by ATC for vectors to cross HOOKK at or above 5000, thence. . . .


TAKEOFF RUNWAY 34: Climb on heading 345° or as assigned by ATC for vectors to cross HOOKK at or above 5000, thence. . . .

. . . . on track 090° to ILEXY, then on transition. Maintain altitude assigned by ATC. Expect filed altitude 10 minutes after departure.

JAYJO TRANSITION (ILEXY4.JAYJO) ZENZI TRANSITION (ILEXY4.ZENZI)

MUCKY THREE DEPARTURE (RNAV)

UNICOM (CTAF) 123.0 AUSTIN DEP CON 119.0 370.85 TOP ALTITUDE: ASSIGNED BY ATC



TAKEOFF MINIMUMS:

Rwy 16: 500-23/4 or standard with minimum climb of 265' per NM to 1500.

Rwy 34: Standard.

NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

NOTE: TAKEOFF Rwy 16 requires a climb to 1700 on

heading 165° prior to turning for obstacle avoidance.

NOTE: Chart not to scale.

21 MAR 2024

2

SC-3, 22 FEB 2024

V

DEPARTURE ROUTE DESCRIPTION


<u>TAKEOFF RUNWAY 16</u>: Climb on heading 165° to 1700, then as assigned by ATC for vectors to cross PAYDA at or above 5000, thence. . .

TAKEOFF RUNWAY 34: Climb on heading 344° or as assigned by ATC for vectors to cross PAYDA at of above 5000, thence

.... on track 279° to MUCKY. Maintain altitude assigned by ATC. Expect filed altitude 10 minutes after departure.



TOP ALTITUDE: ASSIGNED BY ATC



NOTE: RADAR required.

NOTE: DME/DME/IRU or GPS required.

NOTE: RNAV 1.

NOTE: Takeoff Rwy 16 requires a climb to 1700 on heading 165° prior to turning for obstacle avoidance.

NOTE: For DFW terminal area arrivals at FL230 or below only.

TAKEOFF MINIMUMS

Rwy 34: Standard.

Rwy 16: 500-23/4 or standard with minimum climb of 265' per NM to 1500.

NOTE: Chart not to scale.



22 FEB 2024

₫

21 MAR 2024

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 16: Climb on heading 165° to 1700, then as assigned by ATC for vectors to cross MUNCH at or above 5000, thence. . . . TAKEOFF RUNWAY 34: Climb on heading 345° or as assigned by ATC for vectors to cross MUNCH at of above 5000, thence. . . .

. . . . on track 024° to SAYBR. Maintain altitude assigned by ATC. Expect filed altitude 10 minutes after departure.