LOC I-VQR	APP CRS	Rwy ldg	8519
111.9	023°	TDZE	7540
		Apt Elev	7540

ILS or LOC RWY 2

SAN LUIS VALLEY RGNL/BERGMAN FLD (ALS)

NA
-26°C

For inop ALS, increase S-LOC 2 Cats C/D visibility to 1⅜ SM.

MALSR

MISSED APPROACH: Climb to 8700 then climbing right turn to 11000 direct ALS VORTAC and hold, continue climb in hold to 11000.

ASOS	DENVER CENTER	UNICOM
135.175	128.375 379.95	122.8 (CTAF) L



ELEV 7540 D TDZE 7540





CATEGORY	A	B	C	D
S-ILS 2	7740-½ 200 (200-½)			
S-LOC 2	8040-½ 500 (500-½)		8040-1 500 (500-1)	
C CIRCLING	8040-1 500 (500-1)		8080-1½ 540 (600-1½)	8100-2 560 (600-2)
XOGSY FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 2	7880-½ 340 (400-½)			
C CIRCLING	8040-1 500 (500-1)		8080-1½ 540 (600-1½)	8100-2 560 (600-2)

FAF to MAP 5.4 NM

Knots	60	90	120	150	180
Min:Sec	5:24	3:36	2:42	2:10	1:48

SW-1, 22 FEB 2024 to 21 MAR 2024