

WAAS CH 99425 W23A	APP CRS 229°	Rwy Idg 4589 TDZE 45 Apt Elev 45
--	------------------------	---

RNAV (GPS) RWY 23

NUIQSUT (AQT) (PAQT)


▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C (-13°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV NA with Deadhorse altimeter setting. When local altimeter setting not received, use Deadhorse altimeter setting and increase all DA 123 feet and all MDA 140 feet, increase LPV all Cats and LNAV Circling Cat C visibility ¼ mile, increase LNAV/VNAV all Cats and LNAV Cat C visibility ½ mile.

MISSED APPROACH:
Climb to 1700 direct
BIQFI and hold.

ASOS 135.35	ANCHORAGE CENTER 119.4	DEADHORSE RADIO 122.5	CTAF 122.8 0
-----------------------	----------------------------------	---------------------------------	-------------------------------



ELEV 45

TDZE 45

MRL Rwy 5-23 **0**
REIL Rwy 23 **0**

1700	BIQFI	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00°/TCH 33).			
* LNAV only		FIKOR 2 NM to RW23	ETFAF 1700	IQUQU 1700	4 NM Holding Pattern
RW23		720*	229°	049°	GP 3.00° TCH 52
2 NM		3.1 NM	6 NM		
CATEGORY	A	B	C	D	
LPV DA	295-1		250 (300-1)	NA	
LNAV/VNAV DA	369-1		324 (400-1)	NA	
LNAV MDA	480-1	435 (500-1)	480-1 3/8 435 (500-1 3/8)	NA	
CIRCLING	520-1	475 (500-1)	520-1 1/2 475 (500-1 1/2)	NA	

AK, 25 JAN 2024 to 21 MAR 2024

AK, 25 JAN 2024 to 21 MAR 2024