

LOC I-DAB
109.7

APP CRS
070°

Rwy Idg
TDZE
Apt Elev
9810
30
34

ILS or LOC RWY 7L
DAYTONA BEACH INTL (DAB)

⚠

Inoperative table does not apply to S-ILS 07L. Helicopter visibility reduction below RVR 4000 NA. For inop MALSR, increase S-LOC 07L Cat A and B and ZOPRI fix minimums S-LOC 07L all Cats visibility to RVR 5500. Autopilot coupled approach NA below 535.

MALSR

MISSED APPROACH: Climb to 700 then climbing right turn to 3000 on heading 175° and ORL VORTAC R-033 to SMYRA/ORL 33.1 DME and hold.

ATIS 132.875	DAYTONA APP CON 125.8 269.075	DAYTONA TOWER 120.7 257.8	GND CON 121.9 348.6	CLNC DEL 119.3
------------------------	---	-------------------------------------	-------------------------------	--------------------------

DME or RADAR REQUIRED

ELEV 34 **D** TDZE 30

WAMAL OMN 18.9

TIGAE INT OMN 16

FOUG INT RADAR

ZOPRI INT

GS 3.00° TCH 57

1900 070°

1600

1600

*680

3.3 NM

7.7 NM

2.9 NM

1.9 NM

700

3000

ORL R-033

SMYRA INT

*LOC only.

CATEGORY	A	B	C	D
S-ILS 07L	230/40		200 (200-¾)	
S-LOC 07L	680-1	650 (700-¾)	680-1⅞	650 (700-1⅞)
CIRCLING	680-1	646 (700-1)	646 (700-1⅞)	666 (700-2)
ZOPRI FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 07L	380/40		350 (400-¾)	
CIRCLING	540-1	506 (600-1)	680-1¼	700-2
			646 (700-1¼)	666 (700-2)

TDZ/CL Rwy 7L

HIRL Rwy 7L-25R

MIRL Rwy 7R-25L and 16-34

REIL Rwy 7R, 16, 25L and 34

FAF to MAP 4.8 NM

Knots	60	90	120	150	180
Min:Seq	4:48	3:12	2:24	1:55	1:36

DAYTONA BEACH, FLORIDA
Amdt 32A 28FEB19

29°11'N-81°03'W

DAYTONA BEACH INTL (DAB)
ILS or LOC RWY 7L