

LOC/DME I-HUM	APP CRS	Rwy Idg	8950
110.5	042°	TDZE	8
Chan 42		Apt Elev	13

LOC RWY 4R

DANIEL K INOUEY INTL (HNL) (PHNL)

DME required.

▼


▲

Circling Rwy 22R NA at night. For inop ALS, increase Cat E visibility to 1½ SM. Circling NA for Cats A and B northwest of Rwys 8L and 22R. Circling NA for Cats C and D north of Rwy 8L-26R. Circling NA to sea lanes 4W, 8W, 22W, and 26W.

MALSR

MISSED APPROACH: Climbing right turn to 3000 on heading 220° and HNL VORTAC R-171 to ALANA INT/ HNL 13.9 DME and hold.

D-ATIS	HCF APPROACH	HONOLULU TOWER	GND CON	CLNC DEL
127.9 251.15	118.3 269.0	118.1 257.8 123.9 273.575 (Rwy 8R/26L)	121.9 348.6	121.4 281.4



Remain within 15 NM

PERLY I-HUM 6.2

1900

222°

042°

1500

3.03° TCH 55

FALOS HUM 2.7

3000 hdg 220°

HNL R-171

ALANA

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 71°).

3.5 NM

1 NM

CATEGORY	A	B	C	D	E
S-4R	460-¾	452 (500-¾)	460-⅞	452 (500-⅞)	
◼ CIRCLING	680-1¼ 667 (700-1¼)	760-1¼ 747 (800-1¼)	820-2¼ 807 (900-2¼)	1400-3 1387 (1400-3)	NA

MIRL Rwy 4L-22R

REIL Rwys 4L, 8R, 22L, 22R, and 26R

HIRL Rwys 4R-22L, 8L-26R, and 8R-26L

WATER RWYS:

8W-26W 5090 X 300

4W-22W 3000 X 150