

APP CRS
267°

Rwy Idg
TDZE
Apt Elev

9000
96
96

RNAV (RNP) Y RWY 26R

GEORGE BUSH INTCNL/HOUSTON (IAH)

▼

For uncompensated Baro-VNAV systems, procedure NA below -3°C (27°F) or above 54°C (130°F). GPS required. Simultaneous approach authorized. For inop ALS, increase RNP 0.11 all Cats visibility to RVR 5000 and increase RNP 0.15 all Cats visibility to 1½ SM. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSF-2

ALS

2

MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct PEPBI and hold.

D-ATIS 124.05	HOUSTON APP CON 120.05 379.1 EAST 124.35 316.15 WEST	HOUSTON TOWER 120.72 290.2	GND CON 121.7	CLNC DEL 128.1	CPDLC
------------------	--	-------------------------------	------------------	-------------------	-------

SC-5, 22 FEB 2024 to 21 MAR 2024

4 NM

345°

PEPBI

2049

2049

(IF) SKLER
Max 210K
(RF REQD)
6000

5100
087° (3)

DRKAR

2600 to SOOPR
(8.1)

4000
(4.2)

5000
235° (3)

6000
200° (3.2)

(IAF) HOOTI
Max 210K
6000

GRIZL

5000
267° (5)

(IAF) ZAPPO

NEWLY
5000

(IF) RAIDS

3000
(7.2)

2600 to SOOPR
(1.8)

CHUBS

2000
267° (2.6)

(FAF) OWELL

255

258±

399

256

530

635

267°

646

MSA R W 26R 2.5 NM

3100

ELEV 96

D

TDZE 96

267°

9000 X 1.50

8402 X 1.50

2001 X 1.50

1000 X 1.50

33R

33L

422

TWR

600

3000

PEPBI

See planview for multiple IF locations.

RW26R

OWELL

2000

267°

2600

SOOPR

GP 3.00°

TCH 59

5.8 NM

2.6 NM

CATEGORY	A	B	C	D
RNP 0.11 DA		429/40	333 (400-¾)	
RNP 0.15 DA		496/45	400 (400-⅞)	
RNP 0.30 DA		554/50	458 (500-1½)	

TDZ/CL Rwy's 8R, 8L, 15R, 26R, 26L, 27 and 33L
HIRL all Rwy's

AUTHORIZATION REQUIRED

HOUSTON, TEXAS

GEORGE BUSH INTCNL/HOUSTON (IAH)

Orig-D 13SEP18

29°59'N-95°20'W

RNAV (RNP) Y RWY 26R

SC-5, 22 FEB 2024 to 21 MAR 2024