

WAAS CH 45721 W23A	APP CRS 233°	Rwy Idg TDZE 210 Apt Elev 215
--	------------------------	---

RNAV (GPS) RWY 23

EARLY COUNTY (BIJ)

RNP APCH - GPS.

▼



▲

Inop table does not apply to LPV, LNAV/VNAV and LNAV Cat A/B. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Rwy 23 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Bainbridge altimeter setting; increase LPV DA to 578 feet, LNAV/VNAV DA to 587 feet; increase all MDAs 80 feet and visibility LNAV Cat C/D ½ SM and Circling Cat C/D ¼ SM. For inop ALS, increase LNAV Cat C/D visibility to 1 ½ SM. Baro-VNAV and VDP NA when using Bainbridge altimeter setting.

MALSF

MISSED APPROACH:
Climb to 2000 direct
ENUCI and hold.

AWOS-3PT 118.475	CAIRNS APP CON ★ 125.4 327.125	CTAF 122.9 0
----------------------------	--	------------------------




2000		ENUCI	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 30).		4 NM Holding Pattern
*LNAV only.		NINVE 2.5 NM to RWY 23	EARLY 1800	PARGE	3000
1.1 NM to RWY 23		1040	1800	233°	053°
1.1		1.4	2.3 NM	6.7 NM	GP 3.00° TCH 57
CATEGORY	A	B	C	D	
LPV DA		501-1	291 (300-1)		
LNAV/VNAV DA		510-1	300 (300-1)		
LNAV MDA		600-1	390 (400-1)		
CIRCLING	720-1	505 (600-1)	860-1 ¾ 645 (700-1¾)	960-2 ½ 745 (800-2½)	

WAAS CH 61121 W05A	APP CRS 053°	Rwy ldg TDZE 215 Apt Elev 215
--	------------------------	---

RNAV (GPS) RWY 5

EARLY COUNTY (BIJ)

RNP APCH - GPS.			MISSED APPROACH: Climb to 3000 direct PARGE and hold.
▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Rwy 5 helicopter visibility reduction below ¼ SM NA. Baro-VNAV and VDP NA when using Bainbridge altimeter setting. When local altimeter setting not received, use Bainbridge altimeter setting and increase LPV DA to 605 feet and all visibilities ½ SM. Increase LNAV/VNAV DA to 657 feet and all visibilities ¾ SM. Increase all MDA 80 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ¼ SM.			
AWOS-3PT 118.475	CAIRNS APP CON ★ 125.4 327.125	CTAF 122.9 0	



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 34).		3000	PARGE
2000		232°		052°	
GP 3.00° TCH 59		052°		1800	*LNAV only.
		053°		1.5 NM to RWY 5	
		6.7 NM		3.3 NM	1.5 NM
CATEGORY	A	B	C	D	
LPV DA	528-1		313 (400-1)		
LNAV/VNAV DA	580-1		365 (400-1)		
LNAV MDA	740-1	525 (600-1)	740-1½	525 (600-1½)	
CIRCLING	740-1	525 (600-1)	860-1¾ 645 (700-1¾)	960-2½ 745 (800-2½)	

