

LOC I-DZH
109.95

APP CRS
038°

Rwy Idg
TDZE
Apt Elev
5000
316
316

LOC RWY 4
CULPEPER RGNL (CJR)

ADF required.

MISSED APPROACH: Climb to 800 then climbing left turn to 3000 direct CSN VORTAC and hold, continue climb-in-hold to 3000.

AWOS-3
119.325

POTOMAC APP CON
128.525 306.925

CLNC DEL
121.6

UNICOM
123.075 (CTAF) **1**

One Minute Holding Pattern

NISAE GVE 22.9

2600 ← 218°
038° →

038°

1800

3.12°

TCH 40

6 NM

4.4 NM

800

3000

CSN

MSQ NDB

500 X 100

038°

CATEGORY	A	B	C	D
S-4	700-1	384 (400-1)		NA
CIRCLING	920-1 604 (700-1)	960-1 644 (700-1)	960-1 ¾ 644 (700-1 ¾)	NA

ELEV 316

TDZE 316

REIL Rwy 4 and 22 **1**

MIRL Rwy 4-22 **1**

FAF to MAP 4.4 NM

Knots	60	90	120	150	180
Min:Sec	4:24	2:56	2:12	1:46	1:28

CULPEPER, VIRGINIA

Orig-A 20MAY21

38°32'N-77°-52'W

CULPEPER RGNL (CJR)

LOC RWY 4

NDB	MSQ	APP CRS	Rwy Idg	5000
	351	037°	TDZE	316
			Apt Elev	316





NDB RWY 4
CULPEPER RGNL (CJR)

▽

▲

MISSED APPROACH: Climbing left turn to 3000 direct CSN VORTAC and hold, continue climb-in-hold to 3000.

AWOS-3 119.325	POTOMAC APP CON 128.525 306.925	CLNC DEL 121.6	UNICOM 123.075 (CTAF) 0
-------------------	------------------------------------	-------------------	----------------------------




CATEGORY	A	B	C	D
S-4	920-1 604 (700-1)		920-1 3/4 604 (700-1 3/4)	NA
CIRCLING	920-1 604 (700-1)	960-1 644 (700-1)	960-1 3/4 644 (700-1 3/4)	NA

WAAS CH 56306 W22A	APP CRS 218°	Rwy Idg TDZE 315 Apt Elev 316
--	------------------------	---

RNAV (GPS) RWY 22

CULPEPER RGNL (CJR)

RNP APCH. ⚠ When VGSI inoperative, procedure NA at night. Baro-VNAV NA when using Washington Dulles Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 22 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Washington Dulles Intl altimeter setting and increase all DAs/MDAs 80 feet, LPV and LNAV/VNAV all Cats visibility ¼ mile, LNAV Cats C and D visibility ¼ mile.		MISSED APPROACH: Climb to 3000 direct FAXIK and hold.	
AWOS-3 119.325	POTOMAC APP CON 128.525 306.925	CLNC DEL 121.6	UNICOM 123.075 (CTAF) 📻



5000 X 100

REIL Rwy 4 and 22

MIRL Rwy 4-22

CATEGORY	A	B	C
LPV DA	657-1¼ 342 (400-1¼)		
LNAV/VNAV DA	703-1½ 388 (400-1½)		
LNAV MDA	800-1	485 (500-1)	800-1¼ 485 (500-1¼)

CATEGORY	A	B	C
LPV DA	657-1¼ 342 (400-1¼)		
LNAV/VNAV DA	703-1½ 388 (400-1½)		
LNAV MDA	800-1	485 (500-1)	800-1¼ 485 (500-1¼)

WAAS CH 77606 W04A	APP CRS 038°	Rwy Idg TDZE 316 Apt Elev 316
--	------------------------	---

RNAV (GPS) RWY 4

CULPEPER RGNL (CJR)

RNP APCH.


▼

⚠

When VGSI inoperative, procedure NA at night. Baro-VNAV NA when using Washington Dulles Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 4 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Washington Dulles Intl altimeter setting and increase all DAs 73 feet, all MDAs 80 feet, LPV and LNAV/VNAV all Cats visibility ¼ mile, LNAV Cat D visibility ¼ mile.

MISSED APPROACH: Climb to 3000 direct DOYAT and hold.

AWOS-3 119.325	POTOMAC APP CON 128.525 306.925	CLNC DEL 121.6	UNICOM 123.075 (CTAF) 0
--------------------------	---	--------------------------	-----------------------------------



ELEV 316

TDZE 316

REIL Rwy 4 and 22 0

MIRL Rwy 4-22 0

4 NM Holding Pattern

3000 ← 218°
038° →

GP 3.00°
TCH 40

FAXIK

GORLE

RW04

2100

6.1 NM

5.4 NM

3000

DOYAT

CATEGORY	A	B	C	D
LPV DA	610-1 294 (300-1)			
LNAV/VNAV DA	833-1¾ 517 (600-1¾)			
LNAV MDA	820-1 504 (600-1)		820-1½ 504 (600-1½)	

