

LOC I-FOD	APP CRS	Rwy Idg	6547
109.1	063°	TDZE	1107
		Apt Elev	1156

ILS or LOC RWY 6

FORT DODGE RGNL (FOD)

ADF required. RADAR required for procedure entry at SHRLA.

NA

DME from FOD DME. Simultaneous reception of I-FOD and FOD DME required. For inop ALS, increase S-LOC 6 Cat C/D visibility to 1½ SM.

MALSRL

MISSED APPROACH: Climb to 2800 then left turn direct BARRO LOM and hold.

AWOS-3PT 118.775	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 123.0 (CTAF)
---------------------	-----------------------------------	------------------------

ELEV 1156

TDZE 1107

Remain within 10 NM

2800

GS 3.00° TCH 54

2800

063°

243°

2680

4.9 NM

2800

FO

CATEGORY	A	B	C	D
S-ILS 6	1307-½ 200 (200-½)			
S-LOC 6	1600-½	493 (500-½)	1600-1	493 (500-1)
CIRCLING	1600-1 444 (500-1)	1620-1 464 (500-1)	1740-1½ 584 (600-1½)	2080-3 924 (1000-3)

MIRL Rwy 12-30

REIL Rwys 12, 24 and 30

HIRL Rwy 6-24

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

FORT DODGE, IOWA

Amdt 8 14JUL22

42°33'N-94°12'W

FORT DODGE RGNL (FOD)


ILS or LOC RWY 6

WAAS CH 99615 W12A	APP CRS 125°	Rwy Idg TDZE 1128 Apt Elev 1156
--	------------------------	---

RNAV (GPS) RWY 12
FORT DODGE RGNL (FOD)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Visibility reduction by helicopters NA. When local altimeter setting not received, use Webster City altimeter setting: increase LPV DA to 1447 feet and visibility all Cats ¼ SM; increase LNAV/VNAV DA to 1495 feet; increase all MDAs 60 feet and Circling Cat C visibility ¼ SM. VDP and Baro-VNAV NA when using Webster City altimeter setting.	MISSED APPROACH: Climb to 3400 direct KINPE and hold.
---	---

AWOS-3PT 118.775	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 123.0 (CTAF) 0
----------------------------	--	---------------------------------



ELEV 1156		D		TDZE 1128	
4 NM Holding Pattern		CUVPO		PO CIR	
3400 ← 305°		125° →		125° to RWY 12	
GP 3.00°		TCH 51		*1.3 NM to RWY 12	
6 NM		3.8 NM		1.3	
CATEGORY	A	B	C	D	
LPV DA	1405-1 277 (300-1)				
LNAV/VNAV DA	1453-1¼ 325 (300-1¼)				
LNAV MDA	1560-1	432 (500-1)	1560-1¼ 432 (500-1¼)	1560-1½ 432 (500-1½)	
CIRCLING	1560-1 404 (500-1)	1620-1 464 (500-1)	1740-1½ 584 (600-1½)	2080-3 924 (1000-3)	
FORT DODGE, IOWA Amdt 1B 20MAY21					FORT DODGE RGNL (FOD) RNAV (GPS) RWY 12

WAAS CH 82615 W30A	APP CRS 305°	Rwy Idg TDZE 1142 Apt Elev 1156
--	------------------------	---

RNAV (GPS) RWY 30

FORT DODGE RGNL (FOD)

RNP APCH.

▼


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C.

▲

Helicopter visibility reduction below ¼ SM NA. VDP and Baro-VNAV NA when using Webster City altimeter setting. When local altimeter setting not received, use Webster City altimeter setting: increase LPV DA to 1466 feet and all Cats visibility ¼ SM; increase LNAV/VNAV DA to 1516 feet; increase all MDA 60 feet and LNAV Cats C/D and Circling Cat C visibility ¼ SM.

MISSED APPROACH: Climb to 3400 direct CUVPO and hold.

AWOS-3PT 118.775	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 123.0 (CTAF) 0
----------------------------	--	---------------------------------



ELEV 1156 D TDZE 1142

MIRL Rwy 12-30 0
HIRL Rwy 6-24 0
REIL Rwy 12, 24 and 30 0

3400 ↑	CUVPO 				
-----------	--	--	--	--	--

WAAS CH 61015 W06A	APP CRS 063°	Rwy Idg TDZE 1107 Apt Elev 1156
--	------------------------	---

RNAV (GPS) RWY 6

FORT DODGE RGNL (FOD)

RNP APCH.

Baro-VNAV NA when using Webster City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. VDP NA when using Webster City altimeter setting. When local altimeter setting not received, use Webster City altimeter setting: increase LPV DA to 1349 feet; increase LNAV/VNAV DA to 1567 feet and all Cats visibility ¼ SM; increase all MDAs 60 feet and LNAV Cats C/D and Circling Cat C visibility ¼ SM. For inoperative MALSR when using Webster City altimeter setting, increase LPV all Cats visibility to 1 mile.

MALSR

MISSED APPROACH:
Climb to 3000 direct
OXDAH and hold.

AWOS-3PT 118.775	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 123.0 (CTAF)
----------------------------	--	-------------------------------

Enroute chart showing RNP APCH for RNAV (GPS) RWY 6. The chart includes waypoints GEGQI, OGGHU, EYROV, and IQFEF. It shows holding patterns for GEGQI and OGGHU, and a missed approach fix at OXDAH. Altitudes and distances are marked along the flight path.

ELEV 1156

D

TDZE 1107

4 NM Holding Pattern

GP 3.00° TCH 54

3000

243°

063°

GEGQI

EYROV

2800

063°

RW06

1.2 NM to RW06

3000

OXDAH

*1.2 NM to RW06

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	1307-½		200 (200-½)	
LNAV/VNAV DA	1525-1		418 (400-1)	
LNAV MDA	1500-½ 393 (400-½)		1500-1 393 (400-1)	
CIRCLING	1560-1 404 (500-1)	1620-1 464 (500-1)	1740-1½ 584 (600-1½)	2080-3 924 (1000-3)

MIRL Rwy 12-30

HIRL Rwy 6-24

REIL Rwy 12, 24 and 30

FORT DODGE, IOWA

Amdt 1B 20MAY21

42°33'N-94°12'W

FORT DODGE RGNL (FOD)

RNAV (GPS) RWY 6