

MEMPHIS APP CON
119.1 291.6 (176°-355°)
125.8 338.3 (356°-175°)
D-ATIS
127.75

WALNUT RIDGE
114.5 ARG
Chan 92

FL210 290K

15 NM
344°
FL180
164°
(13)

STANI
FL230

HORIS
FL190 290K

15 NM

IGLOO

HUBBL
FL230

DAWGG
280K

FNCHR
Landing North:
16000
14000
Landing South:
10000 230K

GILMORE
113.0 GQE
Chan 77

MEMPHIS
117.5 MEM
Chan 122

BEERT
12000 250K
10000

BOWEN
8000 210K

LOONR
11000 9000

R-308



MARBI
FL180
098°
(34)
278°
15 NM

RAZORBACK
116.4 RZC
Chan 111

NOTE: DME and RADAR required.
NOTE: Procedure not available for RNAV capable Turbojets.
NOTE: RNAV capable Turbojets must file the BRBBQ RNAV STAR.
NOTE: Maintain last assigned altitude until cleared to "descend via the DAWGG TWO," then comply with altitude restrictions as published.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

ARRIVAL ROUTE DESCRIPTION

RAZORBACK TRANSITION (RZC.DAWGG2): From over RZC VORTAC on RZC R-098 to IGLOO, then on GQE R-291 to DAWGG, thence. . . .

WALNUT RIDGE TRANSITION (ARG.DAWGG2): From over ARG VORTAC on R-164 to DAWGG, thence. . . .

LANDING NORTH: From over DAWGG/GQE 17 DME on GQE R-291 to cross FNCHR/GQE 11 DME at or above 14000 and at or below 16000, then on GQE R-291 to GQE VORTAC, then on GQE R-124 and MEM R-308 to JESTI/MEM 27 DME, then on MEM R-308 to cross BEERT/MEM 22 DME at or above 10000 and at or below 12000 and at 250K, then on MEM R-308 to cross LOONR/MEM 12 DME at or above 9000 and at or below 11000, then on MEM R-308 to cross BOWEN/MEM 8 DME at or above 8000 and at 210K, then on heading 180°, expect radar vectors to final approach course.

LANDING SOUTH: From over DAWGG/GQE 17 DME on GQE R-291 to cross FNCHR/GQE 11 DME at 10000 and 230K, then on heading 112°, expect radar vectors to final approach course.

SE-1, 22 FEB 2024 to 21 MAR 2024

SE-1, 22 FEB 2024 to 21 MAR 2024