

APP CRS	Rwy Idg	2801
019°	TDZE	1116
	Apt Elev	1116


RNAV (GPS) RWY 2
JAMES G WHITING MEML FLD (MEY)

RNP APCH - GPS.


Procedure NA at night. Rwy 2 helicopter visibility reduction below 1 SM NA. Use Sioux City altimeter setting, when not received use Denison altimeter setting and increase all MDAs 20 feet and visibility LNAV Cat B ¼ SM, and visibility Circling Cat C ¼ SM.

MISSED APPROACH: Climb to 3200 direct NEUSE and hold.

SUX ASOS 119.45 270.8	SIOUX CITY APP CON ★ 124.6 307.0	UNICOM 122.8 (CTAF) 0
--------------------------	-------------------------------------	--------------------------



4 NM Holding Pattern		UPYAN	TEGTY	3200	NEUSE
6000	←199°		019°→		
3100					
		6.9 NM	3.4 NM		
CATEGORY	A	B	C	D	
LNAV MDA	1840-1	724 (800-1)	1840-2 724 (800-2)	NA	
CIRCLING	1880-1 764 (800-1)	1940-1¼ 824 (900-1¼)	1980-2½ 864 (900-2½)	NA	



NC-3, 22 FEB 2024 to 21 MAR 2024

NC-3, 22 FEB 2024 to 21 MAR 2024