

APP CRS
022°

Rwy ldg **5501**
TDZE **846**
Apt Elev **874**

RNAV (GPS) RWY 2

MCMINN COUNTY (MMI)

RNP APCH - GPS.


▼

▲

Rwy 2 helicopter visibility reduction below 1 SM NA. Straight-in Rwy 2 NA at night. Circling Rwy 2 NA at night. When local altimeter setting not received, use Mc Ghee Tyson altimeter setting and increase all MDAs 120 feet, and LNAV visibility Cats C and D ½ SM, and Circling visibility Cat A ¼ SM and Cat C ½ SM.

MISSED APPROACH:
Climb to 3100 direct
HUVEP and hold.

AWOS-3 125.425	KNOXVILLE APP CON 123.9 353.6	UNICOM 122.8 (CTAF)
--------------------------	---	-------------------------------



5 NM Holding Pattern

ZAGUG

COTKI

HETAK

RW02

3100

HUVEP

6000

4100

202°

022°

022°

3700

3500

3.00°

TCH 40

2.1 NM

4 NM

8.1 NM

CATEGORY	A	B	C	D
LNAV MDA	1600-1 754 (800-1)	1600-1¼ 754 (800-1¼)	1600-2 754 (800-2)	754 (800-2)
CIRCLING	1600-1 726 (800-1)	1600-1¼ 726 (800-1¼)	1600-2 726 (800-2)	1820-3 946 (1000-3)

ELEV 874

TDZE 846

REIL Rwy 2 and 20

MIRL Rwy 2-20

0.8% UP

6450 X 100

022°