

ILS RWY 11 (CAT II & III)
LOUIS ARMSTRONG NEW ORLEANS INTL (MSY)

ALSF-2

MISSED APPROACH: Climb to 800 then climbing right turn to 2000 on heading 130° and on LEV VORTAC R-354 to SAFES INT/LEV 38.5 DME and hold.

AWDAD

7000
093° (13.2)

4000
106° (9.4)

523

286°

2000
106° (6.7)

MUDBG
I-MSY 8.3
RADAR

70
IM

156
153

500
219

112.0 TBD
R-012
Chan 57

IAF
VOODO
I-MSY 24.4
RQR 5.8
R-273

RESERVE
110.8 RQR
Chan 45

ALT MISSED APCH FIX
HARVEY
HRV 114.1
Chan 88

LOCALIZER 109.9
I-MSY
Chan 36

IAF
TIBBY
112.0 TBD
Chan 57

MSA RQR 25 NM
360°
3100
1800
801

114.1 HRV
R-254
Chan 88
SAFE
LEV 38.5

ELEV	4	D	TDZE	4
------	---	---	------	---

Diagram illustrating the layout of RLLS Rwy 2, showing the TDZ/CL Rwy 11, HIRL AII Runways, and various lighting systems (A, H, P, A4, A5) and a TWB 218.

**CATEGORY II & III ILS - SPECIAL AIRCREW
& AIRCRAFT CERTIFICATION REQUIRED**