

WAAS CH 56336 W12A	APP CRS 126°	Rwy Idg 4000 TDZE 541 Apt Elev 547
--	------------------------	---

RNAV (GPS) RWY 12
MUSCATINE MUNI (MUT)

▼ DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA.
▲ VDP and Baro-VNAV NA with Iowa City altimeter setting. When local altimeter setting not received, use Iowa City altimeter setting and increase all DA 76 feet and all MDA 80 feet, increase LPV, LNAV/VNAV all Cats visibility ½ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F).


MISSED APPROACH: Climb to 2700 direct HOVRA and hold.

AWOS-3P
120.625


QUAD CITY APP CON ★
133,275 257.8

CLNC DEL
119.125

UNICOM
122.7 (CTAF) **L**



ELEV	547		TDZE	541
------	-----	--	------	-----



CATEGORY		A	B	C	D
LPV	DA	1207-2½	666 (700-2½)	NA	
LNAV/ VNAV	DA	1223-2½	682 (700-2½)	NA	
LNAV MDA		1140-1	599 (600-1)	NA	
 CIRCLING		1140-1 593 (600-1)	1200-1 653 (700-1)	NA	

