EL CENTRO, CALIFORNIA

RNAV (GPS) RWY 26

EL CENTRO NAF (VRACIU FLD) (KNJK)

WAAS CH 95990 W26A	APCH CRS 259°	Rwy ldg 9503 TDZE -46 Arpt Elev -42	AL-472 [USN]

RNP APCH

Circling to Rwy 30 NA at night.
When tower closed, increase visibility to 1 mile.

MISSED APPROACH: Climb to 500, then climbing left turn to 2300 direct BEENY and hold.

ATIS ★	LOS ANGELES CENTER	TOWER ★	GND CON	CLNC DEL
269.275	128.6 291.7	119.1 360.2	121.9 254.35	340.2

Visibility reduction by helicopters NA.

For uncompensated Baro-VNAV system LNAV/VNAV NA below -14°C (7°F) or above 54°C (129°F)

CAUTION: Extensive civil aircraft operations at Imperial County airport.

R-2510

RW26

138

39

(FAF) CUNSA

IMPERIAL COUNTY

1100 259° (5)

BAGSE 1700

294

1700 296° (7.9)

4 NM

077° 230K

352

257°

HOLD 4000 2300

(IAF/IF) BEENY

2300 077° (7)

CAUTION: Missed approach max 250 KIAS until 500.

IMPERIAL
115.9 IPL
Chan 106

UNITED STATES

MEXICO

CAUTION:
Do not overfly the US-Mexican border.

2526

MSA RW26 25 NM
6700

EMERG SAFE ALT 100 NM 17,000

500 | 2300 | BEENY

BEENY

4 NM Holding Pattern

077° 4000 2300

257° 2300

BAGSE

296°

259° 1700

CUNSA

1100

0.9 NM to RW26

RW26

3.4 NM

GP 3.00°
TCH 55

ELEV -42

TDZE -46



CATEGORY	A	B	C	D
LPV DA	206-¾ 252 (300-¾)			
LNAV/VNAV DA	204-¾ 250 (300-¾)			214-¾ 260 (300-¾)
LNAV MDA	300-1 346 (400-1)			
C CIRCLING	480-1 522 (600-1)		480-1½ 522 (600-1½)	520-2 562 (600-2)

HIRL Rwys 8-26, 12-30

SW-3, 22 FEB 2024 to 21 MAR 2024
SW-3, 22 FEB 2024 to 21 MAR 2024