

WAAS CH 77721 W13A	APP CRS 125°	Rwy Idg TDZE Apt Elev 5501 431 439
--	------------------------	--

RNAV (GPS) RWY 13

KAOLIN FLD (OKZ)

RNP APCH.


T

A

Rwy 13 helicopter visibility reduction below ¾ SM NA.
For uncompensated Baro-VNAV systems, LNAV/VNAV
NA below -15°C or above 54°C.

MISSED APPROACH: Climb to 1100 then climbing left turn to
2900 direct BEYVA and hold.

AWOS-3 120.575	ATLANTA APP CON ★ 124.2 279.6	UNICOM 123.0 (CTAF) 1
--------------------------	---	---------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 38).

4 NM Holding Pattern

6000
2900

GP 3.00°
TCH 45

BEYVA

AYORU

ZUBMO
2.6 NM to RW13

*1.2 NM to RW13

RW13

*1280

7.1 NM

2.6 NM

1.4 NM

1.2

ELEV 439

TDZE 431

1100

2900

BEYVA

*LNAV only.

CATEGORY	A	B	C	D
LPV DA	691-¾	260 (300-¾)		NA
LNAV/VNAV DA	700-⅞	269 (300-⅞)		NA
LNAV MDA	820-1	389 (400-1)	820-1⅛ 389 (400-1⅛)	NA
CIRCLING	1000-1 561 (600-1)	1120-1 681 (700-1)	1240-2¼ 801 (900-2¼)	NA

REIL Rwy 13 1

MIRL Rwy 13-31 1