WAAS CH 86708 W06A	APP CRS 060°	Rwy ldg 5000 TDZE 657 Apt Elev 666

RNAV (GPS) RWY 6
PONTIAC MUNI (PNT)

DME/DME RNP-0.3 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). Baro-VNAV and VDP NA when using Bloomington/Normal altimeter setting. When local altimeter setting not received, use Bloomington/Normal altimeter setting: increase LPV DA to 1138 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1339 feet and all visibilities 1 SM; increase all MDAs 100 feet and Circling Cat C visibility ½ SM. Visibility reduction by helicopters NA.

MISSED APPROACH: Climb to 3000 direct KEJDO and hold.

AWOS-3	CHICAGO CENTER	UNICOM
119.675	123.75 259.1	123.075 (CTAF)



ELEV 666 TDZE 657



CATEGORY	A	B	C	D
LPV DA	1040-1½ 383 (400-1½)			NA
LNAV/VNAV DA	1071-1½ 414 (500-1½)			NA
LNAV MDA	1080-1 423 (500-1)		1080-1¼ 423 (500-1¼)	NA
CIRCLING	1180-1 514 (600-1)	1200-1 534 (600-1)	1320-1¾ 654 (700-1¾)	NA

MIRL Rwy 6-24

EC-3, 22 FEB 2024 to 21 MAR 2024