

RAVENNA, OHIO

AL-5844 (FAA)

24025



WAAS CH 77735 W09A	APP CRS 093°	Rwy Idg 3499 TDZE 1198 Apt Elev 1198
--	------------------------	---

RNAV (GPS) RWY 9
PORTAGE COUNTY (POV)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Akron-Canton Rgnl altimeter setting and increase all DA 50 feet and all MDA 60 feet, increase LNAV Cat C visibility 1/8 mile, LNAV/VNAV all Cats and Circling Cat C visibility 1/4 mile. Baro-VNAV NA with Akron-Canton Rgnl altimeter setting. Helicopter visibility reduction below 1 SM NA. Night landing Cat C: Procedure NA.

MISSED APPROACH: Climb to 4000 direct WHINR and hold.

AWOS-3 118.675	CLEVELAND APP CON★ 125.5 371.875	CLNC DEL 125.65	UNICOM 123.05 (CTAF) 1
--------------------------	--	---------------------------	----------------------------------



CATEGORY	A	B	C	D
LPV DA	1448-1	250 (300-1)		NA
LNAV/VNAV DA	1507-1	309 (400-1)		NA
LNAV MDA	1760-1	562 (600-1)	1760-1 ⁵ / ₈ 562 (600-1 ⁵ / ₈)	NA
 CIRCLING	1760-1 562 (600-1)	1800-1 602 (700-1)	1920-2 722 (800-2)	NA

Diagram of runway 9-27. The runway is labeled "3499 X 75". The heading is "093°". A star symbol is located on the runway. The number "27" is at the right end. The diagram is titled "ELEV 1198" and "TDZE 1198".

RAVENNA, OHIO
Orig-A 26JUN14

41°13'N-81°15'W

PORTAGE COUNTY (POV)
RNAV (GPS) RWY 9

EC-2, 22 FEB 2024 to 21 MAR 2024