

WAAS CH 87130 W35A	APP CRS 353°	Rwy Idg TDZE Apt Elev	5501 580 592
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35

MC GREGOR EXEC (PWG)

RNP APCH - GPS.

Baro-VNAV NA when using Waco Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Waco Rgnl altimeter setting and increase LPV DA to 861 feet; increase LNAV/VNAV DA to 861 feet; increase all MDAs 40 feet and LNAV visibility Cat B ¼ SM, and Circling visibility Cat B/C ¼ SM. Rwy 35 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 2500 direct BLDEE and on track 018° to ACT VORTAC and hold.

AWOS-3PT
135.525

WACO APP CON ★
127.65 352.0

GCO
121.725

UNICOM
122.8 (CTAF) **0**

652

Δ

RW35

1030

Δ

BRUGO

2.2 NM to RW35

Δ 722

Δ 957

Δ 1297

(FAF) HISNI

Δ 2535

2541

Δ

3200

(6-6)

353°

(IF/IAF) ICIDE

173°

353°

4 NM

3200 NoPT

315°

(10-1)

(IAF) BARBA

MISSED APCH FIX

4 NM

018°

018°

(6-4)

WACO ACT

BLDEE

Δ 2550

Procedure NA for arrivals at BARBA on V548 southbound.

MSA RW35 25 NM

3600

ELEV **592**

TDZE **580**

Δ

35

5501

X 75

0.4% UP

Δ

35

353°

MIRL Rwy 17-35

REIL Rwy 17

Δ

35

353°

2500	BLDEE	tr 018°	ACT	HISNI	ICIDE	4 NM Holding Pattern
				3200		
				BRUGO 2.2 NM to RW35		
				1300		
				2.2 NM	5.9 NM	6.6 NM

CATEGORY

A

B

C

D

LPV DA

830-¾

250 (300-¾)

NA

LNAV/VNAV DA

830-¾

250 (300-¾)

NA

LNAV MDA

960-1

380 (400-1)

960-1⅛

380 (400-1⅛)

NA

CIRCLING

1020-1

428 (500-1)

1060-1

468 (500-1)

1300-2

708 (800-2)

NA

WACO, TEXAS
Amdt 1C 15JUN23

31°29'N-97°19'W

MC GREGOR EXEC (PWG)

RNAV (GPS) RWY 35

SC-3, 22 FEB 2024 to 21 MAR 2024

SC-3, 22 FEB 2024 to 21 MAR 2024