

WAAS CH 97412 W36A	APP CRS 004°	Rwy Idg 5151 TDZE 343 Apt Elev 344
--	------------------------	---

RNAV (GPS) RWY 36

READING RGNL/CARL A SPAATZ FLD (RDG)

⚠

Night landing: Rwy 18, 31 NA. Inoperative table does not apply. Baro-VNAV NA when using Harrisburg Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Harrisburg Intl altimeter setting and increase LPV DA to 715 feet and visibility ¼ SM, increase LNAV/VNAV DA to 928 feet and visibility ¼ SM and increase all MDAs 100 feet, and LNAV Cats C and D and Circling Cats B and C visibility ¼ SM.

MALSIF

⚠

3100

MISSED APPROACH: Climb to 3000 direct YEWSU and via 303° to DUMMR and hold, continue climb-in-hold to 3000.

ATIS 127.1	READING APP CON ★ 125.15 257.9	READING TOWER ★ 119.9 (CTAF) 0 288.3	GND CON 121.9	UNICOM 122.95
----------------------	--	--	-------------------------	-------------------------

MISSED APCH FIX

4 NM

115°

295°

DUMMR

Procedure NA for arrival on ETX VOR/DME airway radials 234 CW 260.

928

3000

303°

YEWSU

639±

Δ 640

Δ 461±

Δ 1263

1102

2900

218°

(23.9)

EAST TEXAS
ETX

MSA RW36 25 NM

3100

Procedure NA for arrival on LRP VOR/DME airway radials 030 CW 104.

1390

Δ 1420

710

VISBY

2 NM to RW36

1035

639±

Δ 521

Δ 1351

Δ 586

1070

(FAF)

Δ 1215

739±

1900

(6.1)

SROKA

Procedure NA for arrival on PTW VORTAC airway radials 231 CW 287.

(IAF)

POTTSTOWN
PTW

2700 NoPT

276°

(17)

Procedure NA for arrival on MXE VORTAC airway radials 283 CW 025.

(IAF)

MODENA
MXE

2700 NoPT

336°

(20.3)

4 NM

Procedure NA for arrival on HUMEL (IF/IAF) holding pattern.

2700 NoPT

087°

(17.3)

(IAF)

LANCASTER
LRP

2700 NoPT

184°

004°

184°

004°

2700

ELEV 344

TDZE 343

81

106°

5151 X 150

6350 X 150

TWR 422

36

004°

REIL Rwy 13 and 31

HIRL Rws 13-31 and 18-36

3000	YEWSU	tr	303°	DUMMR	4 NM	HUMEL	Holding Pattern
*LNAV only	VISBY 2 NM to RW36	*1.1 NM to RW36	1900	SROKA	184°	004°	2700
			1020*	1900			GP 3.00° TCH 40
	1.1	0.9	2.7 NM	6.1 NM			
CATEGORY	A	B	C	D			
LPV DA		622-1	279 (300-1)				
LNAV/VNAV DA		835-1¾	492 (500-1¾)				
LNAV MDA		740-1	397 (400-1)		740-1¾	397 (400-1¾)	
CIRCLING	1020-1 676 (700-1)	1080-1 736 (800-1)	1280-2¾ 936 (1000-2¾)	1660-3 1316 (1400-3)			

READING, PENNSYLVANIA

Orig-C 20MAY21

40°23'N - 75°58'W

READING RGNL/CARL A SPAATZ FLD (RDG)

RNAV (GPS) RWY 36