

WAAS CH 40440 W01A	APP CRS 007°	Rwy Idg 6200 TDZE 1276 Apt Elev 1303
--	------------------------	---

RNAV (GPS) RWY 1
WILKES COUNTY (UKF)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV when below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Hicory altimeter setting and increase LPV DA to 1566 feet and LNAV/VNAV DA to 1669 feet and LNAV/VNAV visibility all Cats ¼ SM. Increase all MDAs 100 feet and LNAV visibility Cats C/D ¼ SM and Circling Cat C ½ SM. For inop ALS when using Hicory altimeter setting, increase LPV all Cats visibility to 1 SM. VDP and Baro-VNAV NA when using Hicory altimeter setting.

MALS R



MISSED APPROACH: Climb to 1800 then climbing right turn to 5000 direct HAPRI and hold, continue climb-in-hold to 5000.

AWOS-3
126.625

ATLANTA CENTER
125.15 263.0

UNICOM
122.7 (CTAF) **L**

• 3730

 $\Delta 2709 \pm$ [illegible]

Δ 2253

5 NM Holding Pattern

HAPRI

5000

←187°

007°→

GP 3.00°

TCH 59

IRIVE

3600

007°

3600

JATLO

2.7 NM to RW01

*1 NM to RW01

RW01

*2160

6 NM

4.5 NM

1.7 NM

1 NM

1800

5000

HAPRI

*LNAV only.

CATEGORY		A	B	C	D
LPV	DA	1476-1/2		200 (200-1/2)	
LNAV/ VNAV	DA	1579-5/8		303 (300-5/8)	
LNAV	MDA	1620-1/2 344 (400-1/2)		1620-5/8 344 (400-5/8)	
 CIRCLING		1800-1 497 (500-1)	1880-1 577 (600-1)	1880-1 1/2 577 (600-1 1/2)	2240-3 937 (1000-3)

ELEV 1303		TDZE 1276
-----------	--	-----------